



Specifications:
 Voltage Rating : 250V AC/DC
 Current Rating : 6.5A AC,DC
 Withstand Voltage : 1500V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -40°C~+105°C

Recommended PCB pattern
 THICKNESS=1.6 TO 2.4mm

Circuits	Dimensions		
	Part No	A	B
2P	8.22	5.94	6.84
3P	10.72	8.44	9.34
4P	13.22	10.94	11.84
5P	15.72	13.44	14.34
6P	18.22	15.94	16.84
7P	20.72	18.44	19.34
8P	23.22	20.94	21.84
10P	28.22	25.94	26.84

Part No.	42508W00-NP-B2-**-**
Material	LCP
Color	NATURAL
Brass/Gold&Ni-plated	

GENERAL TOLERANCES	
LINEAR	0.0 ± 0.35
ANGLES	X° REF ± 6°

SCALE:	1:1
APPROVED	
DESIGNER	

东莞市康导新能源科技有限公司
 DONGGUANG KAO NEW ENERGY TECHNOLOGY CO., LTD
 公司网址: www.dgconna.com
 公司地址: 20001769000@qq.com
 公司电话: 0769-86397639
 公司传真: 0769-86392827

PART. NO.:	42508W00-NP-B2-**-**
REV.:	A0
DWG. NO.:	ENDE05
SHEET:	1/1

REV.	A0	REVISION RECORD	DATE	2021.05.30	UNIT:	MM	SIZE:	A4	
新图面发行		2021.05.30		0.00 ± 0.25		X° ± 3°		X° X' ± 2°	
2021.05.30		0.000 ± 0.15		DRAWN		肖坤权		2021.05.30	

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---