

环保物料

Specifications:

Voltage Rating : 250V AC/DC



Current Rating : 3A AC,DC

Withstand Voltage : 800V AC/minute

Contact Resistance : 10mΩ(MAX.)

Insulation Resistance : 1000MΩ(MIN.)

Temperature Range : -25°C~+85°C



**Ordering Information & Specifications**

Part No	Wire Range	Insulation O. D.	Material	Finish
42006TOP-**-L	AWG#28 -#22	1.0~1.5	Phosphor Bronze	Au or Sn

Unit: mm

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	<b>康导新能源</b> 网址: www.dgoonne.com 电话: 0769-85337633 邮箱: 2850176986@qq.com 传真: 0769-85392827	PART. NO: <b>42006TOP-**-L</b>
				LINEAR	ANGLES					APPROVED
AO	新图面发行	2017.06.16	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	肖坤权	2017.06.16	TITLE: <b>2.00mm pitch Crimp Terminal</b>	REV: AO SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	旷淇	2017.06.16		