

环保物料

Specifications:

Voltage Rating : 125V AC/DC






Current Rating : 2A AC,DC

Withstand Voltage : 1250V AC/minute

Contact Resistance : 40mΩ(MAX.)

Insulation Resistance : 1000MΩ(MIN.)

Temperature Range : -40°C~+105°C



Unit: mm

Part No.	Dimensions					
	A	B	C	D	E	F
2P	5.80	2.00	2.20	-	-	4.90
3P	7.80	4.00	3.70	-	-	6.90
4P	9.80	6.00	3.70	-	7.30	8.90
5P	11.80	8.00	3.70	7.40	9.30	10.90
6P	13.80	10.00	3.70	7.40	11.30	12.90
7P	15.80	12.00	3.70	7.40	13.30	14.90
8P	17.80	14.00	3.70	7.40	15.30	16.90
9P	19.80	16.00	3.70	7.40	17.30	18.90
10P	21.80	18.00	3.70	7.40	19.30	20.90
11P	23.80	20.00	3.70	7.40	21.30	22.90
12P	25.80	22.00	3.70	7.40	23.30	24.90
13P	27.80	24.00	3.70	7.40	25.30	26.90
14P	29.80	26.00	3.70	7.40	27.30	28.90
15P	31.80	28.00	3.70	7.40	29.30	30.90

Material	Color
PBT,UL94V-0	Gray

REV.	REVISION RECORD	DATE	UNIT: MM	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
A0	新图面发行	2017.06.16	MM	0.00±0.15	X° ±3°	APPROVED	黎腾	2017.06.16
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DESIGNER	肖坤权	2017.06.16
						DRAWN	旷淇	2017.06.16


康导新能源
 网址: www.dgoonne.com 电话: 0769-85377633
 邮箱: 2860175966@qq.com 传真: 0769-853622627
 TITLE: **2.00mm pitch Single Housing**

PART NO:	42014H00-NP*-PT	
DWG. NO:	ENDE05	
REV:	A0	SHEET: 1/1