

环保物料

Specifications:

Voltage Rating : 250V AC/DC



Current Rating : 3A AC,DC

Withstand Voltage : 800V AC/minute

Contact Resistance : 10mΩ(MAX.)

Insulation Resistance : 1000MΩ(MIN.)

Temperature Range : -25°C~+85°C



Ordering Information & Specifications

<i>Part No</i>	<i>Wire Range</i>	<i>Insulation O. D.</i>	<i>Material</i>	<i>Finish</i>
<i>42006TOP-**-S</i>	<i>AWG#28-#22</i>	<i>1.0~1.5</i>	<i>Phosphor Bronze</i>	<i>Au or Sn</i>

Unit: mm

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	康导新能源 网址: www.dgconne.com 电话: 0769-85337633 邮箱: 2850175988@qq.com 传真: 0769-85392827	PART. NO: 42006TOP-**-S	
				LINEAR	ANGLES					APPROVED	黎腾
A0	新图面发行	2017.06.16	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	肖坤权	2017.06.16	TITLE: 2.00mm pitch Crimp Terminal	REV: A0	SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	旷淇	2017.06.16			