

环保物料

1			2			3			4			5			6			7			8																																																																																		
环保物料																																																																																																							
Specifications: Voltage Rating : 250V AC/DC Current Rating : 3A AC,DC Withstand Voltage : 500V AC/minute Contact Resistance : 20mΩ(MAX.) Insulation Resistance : 1000MΩ(MIN.) Temperature Range : -55°C~+150°C																																																																																																							
Recommended PCB Layout																																																																																																							
Unit: mm												<table><tr><th rowspan="2">Part No.</th><th colspan="3">Dimensions</th></tr><tr><th>A</th><th>B</th><th>C</th></tr><tr><td>1*2P</td><td>2.0</td><td>6.96</td><td>9.09</td></tr><tr><td>1*3P</td><td>4.0</td><td>8.96</td><td>11.09</td></tr><tr><td>1*4P</td><td>6.0</td><td>10.96</td><td>13.09</td></tr><tr><td>1*5P</td><td>8.0</td><td>12.96</td><td>15.09</td></tr><tr><td>1*6P</td><td>10.0</td><td>14.96</td><td>17.09</td></tr><tr><td>1*7P</td><td>12.0</td><td>16.96</td><td>19.09</td></tr><tr><td>1*8P</td><td>14.0</td><td>18.96</td><td>21.09</td></tr><tr><td>1*9P</td><td>16.0</td><td>20.96</td><td>23.09</td></tr><tr><td>1*10P</td><td>18.0</td><td>22.96</td><td>25.09</td></tr><tr><td>1*11P</td><td>20.0</td><td>24.96</td><td>27.09</td></tr><tr><td>1*12P</td><td>22.0</td><td>26.96</td><td>29.09</td></tr><tr><td>1*13P</td><td>24.0</td><td>28.96</td><td>31.09</td></tr><tr><td>1*14P</td><td>28.0</td><td>30.96</td><td>33.09</td></tr><tr><td>1*15P</td><td>30.0</td><td>32.96</td><td>35.09</td></tr><tr><td>1*16P</td><td>32.0</td><td>34.96</td><td>37.09</td></tr><tr><td>1*17P</td><td>34.0</td><td>36.96</td><td>39.09</td></tr><tr><td>1*18P</td><td>36.0</td><td>38.96</td><td>41.09</td></tr><tr><td>1*19P</td><td>38.0</td><td>40.96</td><td>43.09</td></tr><tr><td>1*20P</td><td>40.0</td><td>42.96</td><td>45.09</td></tr></table>									Part No.	Dimensions			A	B	C	1*2P	2.0	6.96	9.09	1*3P	4.0	8.96	11.09	1*4P	6.0	10.96	13.09	1*5P	8.0	12.96	15.09	1*6P	10.0	14.96	17.09	1*7P	12.0	16.96	19.09	1*8P	14.0	18.96	21.09	1*9P	16.0	20.96	23.09	1*10P	18.0	22.96	25.09	1*11P	20.0	24.96	27.09	1*12P	22.0	26.96	29.09	1*13P	24.0	28.96	31.09	1*14P	28.0	30.96	33.09	1*15P	30.0	32.96	35.09	1*16P	32.0	34.96	37.09	1*17P	34.0	36.96	39.09	1*18P	36.0	38.96	41.09	1*19P	38.0	40.96	43.09	1*20P	40.0	42.96	45.09
Part No.	Dimensions																																																																																																						
	A	B	C																																																																																																				
1*2P	2.0	6.96	9.09																																																																																																				
1*3P	4.0	8.96	11.09																																																																																																				
1*4P	6.0	10.96	13.09																																																																																																				
1*5P	8.0	12.96	15.09																																																																																																				
1*6P	10.0	14.96	17.09																																																																																																				
1*7P	12.0	16.96	19.09																																																																																																				
1*8P	14.0	18.96	21.09																																																																																																				
1*9P	16.0	20.96	23.09																																																																																																				
1*10P	18.0	22.96	25.09																																																																																																				
1*11P	20.0	24.96	27.09																																																																																																				
1*12P	22.0	26.96	29.09																																																																																																				
1*13P	24.0	28.96	31.09																																																																																																				
1*14P	28.0	30.96	33.09																																																																																																				
1*15P	30.0	32.96	35.09																																																																																																				
1*16P	32.0	34.96	37.09																																																																																																				
1*17P	34.0	36.96	39.09																																																																																																				
1*18P	36.0	38.96	41.09																																																																																																				
1*19P	38.0	40.96	43.09																																																																																																				
1*20P	40.0	42.96	45.09																																																																																																				
Material LCP,UL94V-0												Color Black												PIN Material Brass																																																																															
康导新能源												康导新能源												康导新能源																																																																															
2.00mm pitch Single Wafer												2.00mm pitch Single Wafer												2.00mm pitch Single Wafer																																																																															
PART NO: 42016W90-1XNPA-A2-RS												PART NO: 42016W90-1XNPA-A2-RS												PART NO: 42016W90-1XNPA-A2-RS																																																																															
DWG. NO: ENDE05												DWG. NO: ENDE05												DWG. NO: ENDE05																																																																															
REV: A0												REV: A0												REV: A0																																																																															
SHEET: 1/1												SHEET: 1/1												SHEET: 1/1																																																																															