

环保物料

[illegible]

Specifications:

Voltage Rating : 250V AC/DC
Current Rating : 3A AC,DC
Withstand Voltage : 1000V AC/minute
Contact Resistance : 20mΩ(MAX.)
Insulation Resistance : 1000MΩ(MIN.)
Temperature Range : -55°C~+150°C

Recommended PCB Layout

Technical drawing of a roof plan. The drawing shows a rectangular layout with dimensions and annotations. The overall width is 6.40, and the overall depth is 2.48. The layout includes a central rectangular area with a width of 1.40 and a depth of 2.00. The distance from the top edge to the central area is 1.50, and the distance from the bottom edge to the central area is 0.41. The distance from the right edge to the central area is 0.90. The distance from the left edge to the central area is 0.41. The drawing also shows a series of rectangular elements arranged in a grid, with a total length of $B \pm 0.1$ and a total width of $A \pm 0.1$. The drawing includes a note "Insulation Temperature" and a dimension $\phi 1.30 \pm 0.25$ indicating a circular feature.

Unit: mm			
Part No.	Dimensions		
	A	B	C
2*2P	2.0	6.96	9.09
2*3P	4.0	8.96	11.09
2*4P	6.0	10.96	13.09
2*5P	8.0	12.96	15.09
2*6P	10.0	14.96	17.09
2*7P	12.0	16.96	19.09
2*8P	14.0	18.96	21.09
2*9P	16.0	20.96	23.09
2*10P	18.0	22.96	25.09
2*11P	20.0	24.96	27.09
2*12P	22.0	26.96	29.09
2*13P	24.0	28.96	31.09
2*14P	28.0	30.96	33.09
2*15P	30.0	32.96	35.09
2*16P	32.0	34.96	37.09
2*17P	34.0	36.96	39.09
2*18P	36.0	38.96	41.09
2*19P	38.0	40.96	43.09
2*20P	40.0	42.96	45.09