

环保物料

主要技术参数 Main Specifications

线 数 (Poles): 02~12/20
接触电阻 (Contact resistance): $\leq 20\text{m}\Omega$
绝缘电阻 (Insulation resistance): $\geq 1000\text{M}\Omega$
额定电压 (Rated voltage): 250V AC DC
额定电流 (Rated current): 3.0A AC DC
耐 电 压 (Withstand Voltage): 1000V AC/minute
温度范围 (Temperature Range): $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

PIN	Dimensions	
	A	B
1*2P	2.50	6.80
1*3P	5.00	9.30
1*4P	7.50	11.80
1*5P	10.00	14.30
1*6P	12.50	16.80
1*7P	15.00	19.30
1*8P	17.50	21.80
1*9P	20.00	24.30
1*10P	22.50	26.80
1*11P	25.00	29.30
1*12P	27.50	31.80
1*20P	47.50	59.30

A	HOUSING	1 PCS	PA66	COLOR:WHITE
ITEM	COMPONENT	Q'TY	MATERIAL	FINISH

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
				0.0±0.35	X° REF±6°	APPROVED	黎腾	2017.06.16
				0.00±0.25	X° ±3°	DESIGNER	肖坤权	2017.06.16
A0	新图面发行	2017.06.16	UNIT: MM	0.00±0.15	X° X'±2°	DRAWN	旷淇	2017.06.16
REV.	REVISION RECORD	DATE	SIZE: A4					

	康 导 新 能 源		PART. NO:	
	网址: www.dgoonne.com 电话: 0769-85337633		22509Y	
	邮箱: 2850175988@qq.com 传真: 0769-85392827		DWG. NO:	
	TITLE: 2.50mmPITCH HOUSING		REV: A0	SHEET: 1/1