




环保物料

产品型号	MODEL	KD25CC/KD30CC/KD35CC
材质&电镀	MATERIAL&PLATING	
螺丝	Screw	M3.0, 钢, 镀镍 Steel,Nickel Plated
端子	Terminal	黄铜, 0.8t 镀锡 Brass,Tin Plated
塑件	Housing	PA66, UL94V-0
电气性能	ELECTRICAL	
额定电压	Rated voltage	300V
额定电流	Rated current	20A
绝缘电阻	Insulation resistance	500M Ω /DC500V
耐电压	Withstanding voltage	AC2000V/1min
使用线径	Wire range	22-14AWG 2.5mm ²
机械性能	MECHANICAL	
温度范围	Temp. range	-40℃~+105℃
扭矩	Torque	0.5N.m 4.4Lb.in



N=Number of Contacts

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 康 导 新 能 源 网址: www.dgonne.com 电话: 0769-85337633 邮箱: 2850175988@qq.com 传真: 0769-85392827	PART. NO: KDTB0241		
				LINEAR	ANGLES					APPROVED	黎腾	2017. 06. 16
				0. 0±0. 35	X° REF±6°	DESIGNER	肖坤权	2017. 06. 16				
A0	新图面发行	2017. 06. 16	UNIT: MM	0. 00±0. 25	X° ±3°					DRAWN	旷淇	2017. 06. 16
REV.	REVISION RECORD	DATE	SIZE: A4	0. 000±0. 15	X° X'±2°							