

环保物料

主要技术参数
Main Specifications

线数 (poles): 2 to 20P
额定电流 (Current rating): 1.0A AC, DC
额定电压 (Voltage rating): 50V AC, DC
温度范围 (Temperature range): -25°C to +85°C
接触电阻 (Contact resistance): $\leq 20\text{m}\Omega$
绝缘电阻 (Insulation resistance): $\geq 100\text{m}\Omega$
耐电压 (Withstand voltage): 500V AC/minute
适用线规 (Applicable wire): AWG #32 to #28

Poles	Dimensions mm	
	A	B
2	1.0	3.5
3	2.0	4.5
4	3.0	5.5
5	4.0	6.5
6	5.0	7.5
7	6.0	8.5
8	7.0	9.5
9	8.0	10.5
10	9.0	11.5
11	10.0	12.5
12	11.0	13.5
13	12.0	14.5
14	13.0	15.5
15	14.0	16.5
16	15.0	17.5
17	16.0	18.5
18	17.0	9.5
19	18.0	20.5
20	19.0	21.5

3	焊片	Phos Bronze tin 磷青铜镀锡	2		本色
2	针脚	Phos Bronze tin 磷青铜镀锡	N		
1	基座	LCP UL94V-0	1		
序号	名称/料号	材 料	每只用量 Each Amount	数量	附 注

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
				0.0 $\pm$ 0.35	X° REF $\pm$ 6°	APPROVED	黎腾	2017.06.16
				0.00 $\pm$ 0.25	X° $\pm$ 3°	DESIGNER	肖坤权	2017.06.16
AO	新图面发行	2017.06.16	UNIT: MM	0.000 $\pm$ 0.15	X° X' $\pm$ 2°	DRAWN	旷淇	2017.06.16
REV.	REVISION RECORD	DATE	SIZE: A4					

	康 导 新 能 源		PART. NO:	
	网址: www.dgconne.com 电话: 0769-85337633 邮箱: 2850175988@qq.com 传真: 0769-85392827		21003AW	
	TITLE:		DWG. NO:	
	1.0mmPITCH 90° WAFER SMT TYPE		REV: AO	SHEET: 1/1