







环保物料



Specifications:
Voltage Rating : 250V AC/DC
Current Rating : 6.5A AC,DC
Withstand Voltage : 1500V AC/minute
Contact Resistance : 10mΩ(MAX.)
Insulation Resistance : 1000MΩ(MIN.)
Temperature Range : -40°C~+105°C

Circuits Part No	Dimensions	
	A	B
2P	7.75	2.50
3P	10.25	5.00
4P	12.75	7.50
5P	15.25	10.00
6P	17.75	12.50
7P	20.25	15.00
8P	22.75	17.50
10P	27.75	22.50

Part No.	Material	Color
42508H00-NPA-G1-4T	PA9T,UL94V-0	BLACK

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUAN KD NEW ENERGY TECHNOLOGY CO., LTD 公司地址: www.dgconne.cn 公司电话: 0769-85337633 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: 42508H00-NPA-G1-9T	
				LINEAR	ANGLES	APPROVED				DWG. NO: ENDE05	
				0.0±0.35	X° REF±6°						
A0	新图面发行	2021.05.30		UNIT: MM	0.00±0.25	X° ±3°	DESIGNER				REV: A0
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.15	X° X'±2°	DRAWN	肖坤权	2021.05.30	TITLE: MOLEX 2.5PH 单排线端塑胶主体（本色）		SHEET: 1/1