

环保物料

左边加肋

The last

NO.1
NO.2

Specifications:
Voltage Rating : 250V AC/DC
Current Rating : 6.5A AC,DC
Withstand Voltage : 1500V AC/minute
Contact Resistance : 10mΩ(MAX.)
Insulation Resistance : 1000MΩ(MIN.)
Temperature Range : -40°C~+105°C

Circuits Part No	Dimensions	
	A	B
2*2P	7.75	2.50
2*3P	10.25	5.00
2*4P	12.75	7.50
2*5P	15.25	10.00
2*6P	17.75	12.50
2*7P	20.25	15.00
2*8P	22.75	17.50
2*10P	27.75	22.50

Part No.	Material	Color
42508H00-2*NP-G1-9T	PA9T,UL94V-0	BLACK

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 东莞市康导新能源科技有限公司 DONGGUANG KD NEW ENERGY TECHNOLOGY CO., LTD 公司地址: www.dgoonne.cn 公司电话: 0769-85337633 邮 箱: 2850175986@qq.com 公司传真: 0769-85392827	PART. NO: 42508H00-2*NP-G1-9T		
				LINEAR	ANGLES	APPROVED						
				0.0±0.35	X° REF±6°							
A0	新图面发行	2021.05.30		UNIT: MM	0.00±0.25	X° ±3°	DESIGNER				TITLE:	ENDE05
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.15	X° X'±2°	DRAWN	肖坤权	2021.05.30	MOLEX 2.5PH 双排线端塑胶主体（黑色）		REV: A0	SHEET: 1/1